World of Coats alcazar

Coats *alcazar* is a viscose rayon embroidery thread for machine embroidering. Its superior lustre and smooth operation at the highest speeds have made it a popular choice among embroidery customers.

Main Uses:

- · General purpose embroidery
- · Delicate fabrics and laces
- · Fleece, knit and cotton tops
- · Small letters and detailing
- · Appliqué embroidery



Features and Benefits:

- ullet Coats ${\it alcazar}$ is a viscose rayon thread for machine embroidering
- Produced using the most advanced technology to guarantee optimum performance
- · Exceptional consistency to deliver outstanding sewability
- Attractive lustre and extensive range of colours
- Engineered for sewing at the highest speeds
- Certified to Öko-Tex Standard 100, class 1, the most stringent class covering baby wear

World of Coats

- $\bullet \ \ Coats is the largest global \ thread \ supplier \ and \ has \ been \ the \ world's \ leading \ thread \ company \ for \ over \ 200 \ years.$
- With manufacturing plants in over 40 locations and sales and distribution in more than 60 countries, Coats is uniquely placed to serve your thread needs anywhere in the world.
- Our state of the art colour communications management system, Coats ColourTalk®, enables exact sample matching and colour approval almost instantaneously between locations around the globe.

One colour range. One specification. Worldwide.

Coats operates to a global specification for Coats *alcazar* with quality audited by a centrally located team.





VISCOSE RAYON

roduct ntormatio



Global Offer Tex. no.	Total Dtex	Ply	Target strength in grams	Elongation% min - max	Recommended needle size* Singer/Metric
27	290	2	560	15 - 19	9 / 65

(*Needle size recommendations are a guide only and ultimately depend on the sewing application)



Physical and chemical properties of viscose rayon:

Chemical Properties

Mineral acids: Resistant to medium acids
 Alkalis: Resistant to medium alkalis
 Organic solvents: Resistant to most solvents

Bleaching: Unaffected in domestic conditions

• Laundering /

dry cleaning: Unaffected



Coats alcazar fastness properties

Wash Fastness (ISO 105 CO4 / AATCC 64 - 96) Grade 4
 Rub Fastness (ISO 105 X12 / AATCC 8 - 86) Grade 4
 Perspiration Fastness (ISO 105 EO4 / AATCC 15 - 94) Grade 4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)















VISCOSE RAYON

